

PRODUCT

Collection	Luxe by Lint Tile
Construction	SPC
Wear Layer	20 mil (0.5mm.)
Thickness	4mm + 1mm pad
Attached Cushion	1mm IXPE
Installation	Floating
Locking System	Unilin™

FEATURES

Bevel	Painted Bevel Edge
Texture	Standard Emboss
Material	100% Virgin, Phthalate Free
Plank Size	7"x48"

PERFORMANCE

Impact Sound Conduction	ASTM E492-09	63
Sound Transmission Class	ASTM E90-09	65
Slip Resistance	ASTM D 2047	>0.8 Exceeds, Low Risk
Dimensional Stability	ASTM F2199	Passes, Less than 0.02"/ft
Residual Indentation	F1914	Passes, No Indentation
Static Load Limit	ASTMF970	Passes
Flexibility	ASTM F137	Passes
Resistance to Heat	ASTM F 1514	Passes
Resistance to Light	ASTM 1515	Passes
Resistance to Chemicals	ASTM F 925	5 min = Passes, 24 hr = Passes
Radiant Flux	ASTM 648	Exceeds, Class 1
Smoke Density	ASTM E662	Passes

TECHNICAL INFORMATION

For warranties, installation and maintenance instructions, contact your Lint Tile Sales Representative