

MACH I



PILOT



PARACHUTE



BOGEY



AVIATOR



DOG FIGHT

MACH I SPECIFICATIONS

PACKAGING

| PRODUCT DESCRIPTION | PCS/CTN | SF/CTN | SF/PLT | CTNS/PLT | DEPTH | PLT/CTNR | CTNS/CTNR | SF/CTNR | PLT SIZE |
|---|---------|--------|----------|----------|-------|----------|-----------|---------|-------------|
| 7" × 48" - Light Commercial 100% Virgin Anti-microbial LVP | 14 | 32.7 | 2,779.50 | 85 | 2 mm | 20 | 1700 | 55,590 | 49"x40"x40" |

PRODUCT

PERFORMANCE

| COLLECTION | MACH I | TEST PERFORMED | ASTM | RATING | | | |
|----------------------|---|-------------------------|-----------|-------------------------------------|------|------|------|
| CONSTRUCTION | Dimensionally Stable Core | SIZE | THICKNESS | F2055 | F386 | PASS | PASS |
| FINISH | ArmourGuard Microbead Technology | SQUARENESS | F2055 | PASS | | | |
| WEAR LAYER | 8 mil | DIMENSIONAL STABILITY | F2199 | PASS 0.011 in / ft | | | |
| THICKNESS | 2 mm | RESIDUAL INDENTATION | F1914 | PASS | | | |
| ATTACHED CUSHION | No | STATIC LOAD LIMIT | F970 | PASS 1000 psi / 250 psi | | | |
| INSTALLATION | Direct Glue / PSA | FLEXIBILITY | F137 | PASS | | | |
| COLORS | Pilot, Parachute, Bogey, Aviator, Dog Fight | RESISTANCE TO HEAT | F1514 | PASS < 8 (delta E) | | | |
| ENVIRONMENTAL | | RESISTANCE TO LIGHT | 1515 | PASS < 8 (delta E) | | | |
| INDOOR AIR QUALITY | Floor Score | RESISTANCE TO CHEMICALS | F925 | PASS | | | |
| WARRANTY | | CRITICAL RADIANT FLUX | E648 | CLASS 1 (< 0.45 w/cm ²) | | | |
| RESIDENTIAL | See Representative | OPTICAL SMOKE DENSITY | E662 | PASS <450 | | | |
| LIGHT COMMERCIAL | See Representative | SLIP RESISTANCE | C1028 | PASS (> 0.50) | | | |



LINT TILE

111 NOTCH LANE WENDEL, PA 15691

P: 800-245-5564 F: 724-446-9252

www.linttile.com