

MACH II



MACH II SPECIFICATIONS

PACKAGING

PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	CTNS/CTNR	SF/CTNR	PLT SIZE
7" × 48" - Light Commercial 100% Virgin Anti-microbial LVP	15	35	2100	60	2.5 mm	20	1200	42,000	49"x40"x40"

PRODUCT

PERFORMANCE

COLLECTION	MACH II	TEST PERFORMED	ASTM	RATING			
CONSTRUCTION	Dimensionally Stable Core	SIZE	THICKNESS	F2055	F386	PASS	PASS
FINISH	ArmourGuard Microbead Technology	SQUARENESS	F2055	PASS			
WEAR LAYER	12 mil	DIMENSIONAL STABILITY	F2199	PASS 0.011 in / ft			
THICKNESS	2.5 mm	RESIDUAL INDENTATION	F1914	PASS			
ATTACHED CUSHION	No	STATIC LOAD LIMIT	F970	PASS 1000 psi / 250 psi			
INSTALLATION	Direct Glue / PSA	FLEXIBILITY	F137	PASS			
COLORS	Super Sonic, Ripcord, Bandit, Fragged, Combat, Fuselage	RESISTANCE TO HEAT	F1514	PASS < 8 (delta E)			
ENVIRONMENTAL		RESISTANCE TO LIGHT	1515	PASS < 8 (delta E)			
INDOOR AIR QUALITY	Floor Score	RESISTANCE TO CHEMICALS	F925	PASS			
WARRANTY		CRITICAL RADIANT FLUX	E648	CLASS 1 (< 0.45 w/cm2)			
RESIDENTIAL	See Representative	OPTICAL SMOKE DENSITY	E662	PASS <450			
LIGHT COMMERCIAL	See Representative	SLIP RESISTANCE	C1028	PASS (> 0.50)			



LINT TILE

111 NOTCH LANE WENDEL, PA 15691

P: 800-245-5564 F: 724-446-9252

www.linttile.com