

MACH III



MACH III SPECIFICATIONS

PACKAGING

PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	CTNS/CTNR	SF/CTNR	PLT SIZE
7" x 48" - Heavy Commercial LVP	12	28	1820	65	3 mm	20	1300	36,400	49"x40"x40"
36" x 36" Heavy Commercial Tile	6	54	1890	35		19	665	35,910	37"x37"x30"
18" x 36" Heavy Commercial Tile	10	45	1890	42		19	798	35,910	40"x40"x40"

PRODUCT

PERFORMANCE

COLLECTION	MACH III	TEST PERFORMED		ASTM		RATING	
CONSTRUCTION	Dimensionally Stable Core	SIZE	THICKNESS	F2055	F386	PASS	PASS
FINISH	ArmourGuard Microbead Technology	SQUARENESS		F2055		PASS	
WEAR LAYER	20 mil (.5mm)	DIMENSIONAL STABILITY		F2199		PASS 0.011 in / ft	
THICKNESS	3 mm	RESIDUAL INDENTATION		F1914		PASS	
ATTACHED CUSHION	No	STATIC LOAD LIMIT		F970		PASS 1000 psi / 250 psi	
INSTALLATION	Direct Glue / PSA	FLEXIBILITY		F137		PASS	
COLORS	Falcon, Tomcat, Hellfire, Stealth, Lightning, Hornet, Raptor, Golden Eagle, Sound Barrier, Ghost Rider (T), Punch Out (T), Winchester (T), Tailhook (T) and Typhoon (T)	RESISTANCE TO HEAT		F1514		PASS < 8 (delta E)	
ENVIRONMENTAL		RESISTANCE TO LIGHT		1515		PASS < 8 (delta E)	
INDOOR AIR QUALITY	Floor Score	RESISTANCE TO CHEMICALS		F925		PASS	
WARRANTY		CRITICAL RADIANT FLUX		E648		CLASS 1 (< 0.45 w/cm2)	
RESIDENTIAL	See Representative	OPTICAL SMOKE DENSITY		E662		PASS <450	
LIGHT COMMERCIAL	See Representative	SLIP RESISTANCE		C1028		PASS (> 0.50)	



111 NOTCH LANE WENDEL, PA 15691
P: 800-245-5564 F: 724-446-9252
www.linttile.com