

# LUXE XL



## LUXE XL SPECIFICATIONS

### PACKAGING

PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
9" x 60" - Painted Bevel Edge EIR Emboss, Aluminum Oxide Scratch Protection	7	26.24	1574.40	60	5.5mm	17	26,764.80	N/A	N/A

### PRODUCT

### PERFORMANCE

COLLECTION	LUXE XL	TEST PERFORMED	ASTM	RATING
CONSTRUCTION	Rigid Core, Waterproof	IMPACT SOUND CONDUCTION	E492-09	63
LOCKING SYSTEM	Unilin™	SOUND TRANSMISSION CLASS	E90-09	65
WEAR LAYER	20 mil (.5mm)	SLIP RESISTANCE	D2047	>0.8 Low Risk
THICKNESS	4.5mm + 1mm pad	DIMENSIONAL STABILITY	F2199	PASS <.02"/ft
ATTACHED CUSHION	1mm IXPE	RESIDUAL INDENTATION	F1914	PASS
INSTALLATION	Floating	STATIC LOAD LIMIT	F970	PASS
COLORS	Yellowstone, Yosemite, Reclaimed, Sequoia, Shenandoah, Morning Dew, Glacier, Vineyard and Sunset	FLEXIBILITY	F137	PASS
<b>ENVIRONMENTAL</b>		RESISTANCE TO HEAT	F1514	PASS
INDOOR AIR QUALITY	UL Greenguard	RESISTANCE TO LIGHT	1515	PASS
<b>WARRANTY</b>		RESISTANCE TO CHEMICALS	F925	5min - PASS   24hr - PASS
RESIDENTIAL	35YRS	RADIANT FLUX	648	EXCEEDS CLASS 1
COMMERCIAL	30YRS	SMOKE DENSITY	E662	PASS



# LINT TILE

111 NOTCH LANE WENDEL, PA 15691

P: 800-245-5564 F: 724-446-9252

www.linttile.com