



MACH II

MACH II Super Sonic

Super Sonic
17.5x120cm / 7"x48"
12mil Wear Layer

COLOR DISPLAYED ON FRONT

MACH II Fragged

Fragged
17.5x120cm / 7"x48"
12mil Wear Layer

COLOR DISPLAYED ON FRONT

MACH II Bandit

Bandit
17.5x120cm / 7"x48"
12mil Wear Layer

COLOR DISPLAYED ON FRONT

MACH II Fuselage

Fuselage
17.5x120cm / 7"x48"
12mil Wear Layer

COLOR DISPLAYED ON FRONT

MACH II Ripcord

Ripcord
17.5x120cm / 7"x48"
12mil Wear Layer

COLOR DISPLAYED ON FRONT

MACH II Combat

Combat
17.5x120cm / 7"x48"
12mil Wear Layer

COLOR DISPLAYED ON FRONT

MACH II SPECIFICATIONS

MACH II SPECIFICATIONS									
PACKAGING									
PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	CTNS/CTNR	SF/CTNR	PLT SIZE
7" x 48" - Light Commercial 100% Virgin Anti-microbial LVP	14	32.7	2779.5	85	2 mm	20	1700	55,590	49"x40"x40"
PRODUCT					PERFORMANCE				
COLLECTION	MACH II			TEST PERFORMED		ASTM		RATING	
CONSTRUCTION	Dimensionally Stable Core			SIZE	THICKNESS	F2055	F386	PASS	PASS
FINISH	ArmourGuard Microbead Technology			SQUARENESS		F2055		PASS	
WEAR LAYER	12 mil			DIMENSIONAL STABILITY		F2199		PASS 0.011 in / ft	
THICKNESS	2 mm			RESIDUAL INDENTATION		F1914		PASS	
ATTACHED CUSHION	No			STATIC LOAD LIMIT		F970		PASS 1000 psi / 250 psi	
INSTALLATION	Direct Glue / PSA			FLEXIBILITY		F137		PASS	
COLORS	Super Sonic, Ripcord, Bandit, Fragged, Combat, Fuselage			RESISTANCE TO HEAT		F1514		PASS < 8 (delta E)	
ENVIRONMENTAL				RESISTANCE TO LIGHT		1515		PASS < 8 (delta E)	
INDOOR AIR QUALITY	Floor Score			RESISTANCE TO CHEMICALS		F925		PASS	
WARRANTY				CRITICAL RADIANT FLUX		E648		CLASS 1 (< 0.45 w/cm2)	
RESIDENTIAL	See Representative			OPTICAL SMOKE DENSITY		E662		PASS <450	
LIGHT COMMERCIAL	See Representative			SLIP RESISTANCE		C1028		PASS (> 0.50)	



221 Lint Lane Irwin, PA 15642 • P: 800-245-5564 F: 724-446-9252 • www.linttile.com



SCAN ME