



**MACH II**  
Super Sonic

Super Sonic  
17.5x120cm / 7"x48"  
12mil Wear Layer

COLOR DISPLAYED ON FRONT

**MACH II**  
Fragged

Fragged  
17.5x120cm / 7"x48"  
12mil Wear Layer

COLOR DISPLAYED ON FRONT

**MACH II**  
Bandit

Bandit  
17.5x120cm / 7"x48"  
12mil Wear Layer

COLOR DISPLAYED ON FRONT

**MACH II**  
Fuselage

Fuselage  
17.5x120cm / 7"x48"  
12mil Wear Layer

COLOR DISPLAYED ON FRONT

**MACH II**  
Ripcord

Ripcord  
17.5x120cm / 7"x48"  
12mil Wear Layer

COLOR DISPLAYED ON FRONT

**MACH II**  
Combat

Combat  
17.5x120cm / 7"x48"  
12mil Wear Layer

COLOR DISPLAYED ON FRONT

**MACH II SPECIFICATIONS**

MACH II SPECIFICATIONS										
PRODUCT DESCRIPTION		PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	CTNS/CTNR	SF/CTNR	PLT SIZE
7" x 48" - Light Commercial 100% Virgin Anti-microbial LVP		14	32.7	2779.5	85	2 mm	20	1700	55,590	49"x40"x40"
PRODUCT					PERFORMANCE					
COLLECTION	MACH II			TEST PERFORMED		ASTM		RATING		
CONSTRUCTION	Dimensionally Stable Core			SIZE	THICKNESS	F2055	F386	PASS	PASS	
FINISH	ArmourGuard Microbead Technology			SQUARENESS		F2055		PASS		
WEAR LAYER	12 mil			DIMENSIONAL STABILITY		F2199		PASS 0.011 in / ft		
THICKNESS	2 mm			RESIDUAL INDENTATION		F1914		PASS		
ATTACHED CUSHION	No			STATIC LOAD LIMIT		F970		PASS 1000 psi / 250 psi		
INSTALLATION	Direct Glue / PSA			FLEXIBILITY		F137		PASS		
COLORS	Super Sonic, Ripcord, Bandit, Fragged, Combat, Fuselage			RESISTANCE TO HEAT		F1514		PASS < 8 (delta E)		
ENVIRONMENTAL				RESISTANCE TO LIGHT		1515		PASS < 8 (delta E)		
INDOOR AIR QUALITY	Floor Score			RESISTANCE TO CHEMICALS		F925		PASS		
WARRANTY				CRITICAL RADIANT FLUX		E648		CLASS 1 (< 0.45 w/cm2)		
RESIDENTIAL	See Representative			OPTICAL SMOKE DENSITY		E662		PASS <450		
LIGHT COMMERCIAL	See Representative			SLIP RESISTANCE		C1028		PASS (> 0.50)		



221 Lint Lane Irwin, PA 15642 • P: 800-245-5564 F: 724-446-9252 • www.linttile.com



SCAN ME