




# MACH III

**MACH III**  
Falcon 90  
Falcon 90  
17.5x120cm / 7"x48"  
20mil Wear Layer



**MACH III**  
Tomcat 93  
Tomcat 93  
17.5x120cm / 7"x48"  
20mil Wear Layer



**MACH III**  
Hellfire 77  
Hellfire 77  
17.5x120cm / 7"x48"  
20mil Wear Layer



**MACH III**  
Lightning 95  
Lightning 95  
17.5x120cm / 7"x48"  
20mil Wear Layer



**MACH III**  
Stealth 74  
Stealth 74  
17.5x120cm / 7"x48"  
20mil Wear Layer



**MACH III**  
Hornet 92  
Hornet 92  
17.5x120cm / 7"x48"  
20mil Wear Layer



**MACH III**  
Raptor 91  
Raptor 91  
17.5x120cm / 7"x48"  
20mil Wear Layer



**MACH III**  
Golden Eagle 94  
Golden Eagle 94  
17.5x120cm / 7"x48"  
20mil Wear Layer



**MACH III**  
Sound Barrier 76  
Sound Barrier 76  
17.5x120cm / 7"x48"  
20mil Wear Layer



**MACH III**  
Ghost Rider T90  
Ghost Rider T90



Ghost Rider T90  
90x90cm / 36"x36"  
20mil Wear Layer

**MACH III**  
Punch Out T92  
Punch Out T92



Punch Out T92  
45x90cm / 18"x36"  
20mil Wear Layer

Also Available: Winchester T93  
45x90cm / 18"x36"  
20mil Wear Layer

COLOR DISPLAYED ON FRONT

Also Available: Tailhook T94  
45x90cm / 18"x36"  
20mil Wear Layer

COLOR DISPLAYED ON FRONT

Also Available: Typhoon T91  
90x90cm / 36"x36"  
20mil Wear Layer

COLOR DISPLAYED ON FRONT

## MACH III SPECIFICATIONS

PACKAGING									
PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	CTN/CTNR	SF/CTNR	PLT SIZE
7" x 48" - Heavy Commercial LVP	12	28	1820	65	3 mm	20	1300	36,400	49"x40"x40"
36" x 36" Heavy Commercial Tile	6	54	1890	35		19	665	35,910	37"x37"x30"
18" x 36" Heavy Commercial Tile	10	45	1890	42		19	798	35,910	40"x40"x40"
PRODUCT					PERFORMANCE				
<b>COLLECTION</b>	MACH III			<b>TEST PERFORMED</b>		<b>ASTM</b>		<b>RATING</b>	
<b>CONSTRUCTION</b>	Dimensionally Stable Core			<b>SIZE</b>	<b>THICKNESS</b>	F2055	F386	PASS	PASS
<b>FINISH</b>	ArmourGuard Microbead Technology			<b>SQUARENESS</b>		F2055		PASS	
<b>WEAR LAYER</b>	20 mil (.5mm)			<b>DIMENSIONAL STABILITY</b>		F2199		PASS 0.011 in / ft	
<b>THICKNESS</b>	3 mm			<b>RESIDUAL INDENTATION</b>		F1914		PASS	
<b>ATTACHED CUSHION</b>	No			<b>STATIC LOAD LIMIT</b>		F970		PASS 1000 psi / 250 psi	
<b>INSTALLATION</b>	Direct Glue / PSA			<b>FLEXIBILITY</b>		F137		PASS	
<b>COLORS</b>	Falcon, Tomcat, Hellfire, Stealth, Lightning, Hornet, Raptor, Golden Eagle, Sound Barrier, Ghost Rider (T), Punch Out (T), Winchester (T), Tailhook (T) and Typhoon (T)			<b>RESISTANCE TO HEAT</b>		F1514		PASS < 8 (delta E)	
<b>ENVIRONMENTAL</b>				<b>RESISTANCE TO LIGHT</b>		1515		PASS < 8 (delta E)	
<b>INDOOR AIR QUALITY</b>	Floor Score			<b>RESISTANCE TO CHEMICALS</b>		F925		PASS	
<b>WARRANTY</b>				<b>CRITICAL RADIANT FLUX</b>		E648		CLASS 1 (< 0.45 w/cm2)	
<b>RESIDENTIAL</b>	See Representative			<b>OPTICAL SMOKE DENSITY</b>		E662		PASS <450	
<b>LIGHT COMMERCIAL</b>	See Representative			<b>SLIP RESISTANCE</b>		C1028		PASS (> 0.50)	



221 Lint Lane Irwin, PA 15642 • P: 800-245-5564 F: 724-446-9252 • www.linttile.com



SCAN ME