




MACH III

MACH III
Falcon 90
Falcon 90
17.5x120cm / 7"x48"
20mil Wear Layer



MACH III
Tomcat 93
Tomcat 93
17.5x120cm / 7"x48"
20mil Wear Layer



MACH III
Hellfire 77
Hellfire 77
17.5x120cm / 7"x48"
20mil Wear Layer



MACH III
Lightning 95
Lightning 95
17.5x120cm / 7"x48"
20mil Wear Layer



MACH III
Stealth 74
Stealth 74
17.5x120cm / 7"x48"
20mil Wear Layer



MACH III
Hornet 92
Hornet 92
17.5x120cm / 7"x48"
20mil Wear Layer



MACH III
Raptor 91
Raptor 91
17.5x120cm / 7"x48"
20mil Wear Layer



MACH III
Golden Eagle 94
Golden Eagle 94
17.5x120cm / 7"x48"
20mil Wear Layer



MACH III
Sound Barrier 76
Sound Barrier 76
17.5x120cm / 7"x48"
20mil Wear Layer



MACH III
Ghost Rider T90



Ghost Rider T90
90x90cm / 36"x36"
20mil Wear Layer

MACH III
Punch Out T92



Punch Out T92
45x90cm / 18"x36"
20mil Wear Layer

Also Available: Winchester T93
45x90cm / 18"x36"
20mil Wear Layer

COLOR DISPLAYED ON FRONT

Also Available: Tailhook T94
45x90cm / 18"x36"
20mil Wear Layer

COLOR DISPLAYED ON FRONT

Also Available: Typhoon T91
90x90cm / 36"x36"
20mil Wear Layer

COLOR DISPLAYED ON FRONT

MACH III SPECIFICATIONS

PACKAGING									
PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	CTN/CTNR	SF/CTNR	PLT SIZE
7" x 48" - Heavy Commercial LVP	12	28	1820	65	3 mm	20	1300	36,400	49"x40"x40"
36" x 36" Heavy Commercial Tile	6	54	1890	35		19	665	35,910	37"x37"x30"
18" x 36" Heavy Commercial Tile	10	45	1890	42		19	798	35,910	40"x40"x40"
PRODUCT					PERFORMANCE				
COLLECTION	MACH III			TEST PERFORMED		ASTM		RATING	
CONSTRUCTION	Dimensionally Stable Core			SIZE	THICKNESS	F2055	F386	PASS	PASS
FINISH	ArmourGuard Microbead Technology			SQUARENESS		F2055		PASS	
WEAR LAYER	20 mil (.5mm)			DIMENSIONAL STABILITY		F2199		PASS 0.011 in / ft	
THICKNESS	3 mm			RESIDUAL INDENTATION		F1914		PASS	
ATTACHED CUSHION	No			STATIC LOAD LIMIT		F970		PASS 1000 psi / 250 psi	
INSTALLATION	Direct Glue / PSA			FLEXIBILITY		F137		PASS	
COLORS	Falcon, Tomcat, Hellfire, Stealth, Lightning, Hornet, Raptor, Golden Eagle, Sound Barrier, Ghost Rider (T), Punch Out (T), Winchester (T), Tailhook (T) and Typhoon (T)			RESISTANCE TO HEAT		F1514		PASS < 8 (delta E)	
ENVIRONMENTAL				RESISTANCE TO LIGHT		1515		PASS < 8 (delta E)	
INDOOR AIR QUALITY	Floor Score			RESISTANCE TO CHEMICALS		F925		PASS	
WARRANTY				CRITICAL RADIANT FLUX		E648		CLASS 1 (< 0.45 w/cm2)	
RESIDENTIAL	See Representative			OPTICAL SMOKE DENSITY		E662		PASS <450	
LIGHT COMMERCIAL	See Representative			SLIP RESISTANCE		C1028		PASS (> 0.50)	



221 Lint Lane Irwin, PA 15642 • P: 800-245-5564 F: 724-446-9252 • www.linttile.com



SCAN ME