



# PRO PLUS

## PRO PLUS Boardwalk

Boardwalk  
17.5x120cm / 7"x48"  
12mil Wear Layer

COLOR DISPLAYED ON FRONT

## PROPLUS Coastline

Coastline  
17.5x120cm / 7"x48"  
12mil Wear Layer

COLOR DISPLAYED ON FRONT

### PRO PLUS SPECIFICATIONS

PACKAGING									
PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
7" x 48" - Micro Bevel Standard Emboss, 100% Virgin Phthalate Free	12	28.36	1701.6	60	4.2mm	20	34.026	50"x40"x40"	45,000
PRODUCT					PERFORMANCE				
<b>COLLECTION</b>	ProPlus				<b>TEST PERFORMED</b>	ASTM/ISO		<b>RATING</b>	
<b>CONSTRUCTION</b>	Rigid Core SPC + EVA				<b>DIMENSIONAL STABILITY</b>	ISO 23999		≤1.67mm/m	
<b>LOCKING SYSTEM</b>	14F				<b>ABRASION RESISTANCE</b>	ASTM D3884		AC2	
<b>WEAR LAYER</b>	12 mil				<b>APPLICATION</b>	EN ISO 10874		22+	
<b>THICKNESS</b>	3.2mm SPC + 1mm EVA PAD				<b>WEAR AND SCRATCH RESISTANCE</b>	ISO45862-2		Rating 4	
<b>ATTACHED CUSHION</b>	1mm EVA				<b>HEAT WARPAGE</b>	ASTM D3884 with H18		≤1.0mm(0.2mm)	
<b>INSTALLATION</b>	Floating				<b>SHRINKAGE</b>	ASTM D3884 with H18		0.08%	
<b>COLORS</b>	Boardwalk, Coastline				<b>CLICK TENSION FORCE</b>	ISO 24334		≥125N/150mm, 168 N/150mm	
<b>ENVIRONMENTAL</b>					<b>DELAMINATION</b>	ASTM D3884 with H18		OK( No Layered)	
<b>INDOOR AIR QUALITY</b>	UL Greenguard				<b>WEAR LAYER</b>	EN ISO 24346		AC2	
<b>WARRANTY</b>					<b>WEIGHT</b>	EN ISO 24342		6.69 kg/m2	
<b>RESIDENTIAL</b>	15YRS				<b>PRODUCT THICKNESS</b>	EN ISO 23447		4.2mm (.17 in.)	
<b>LIGHT COMMERCIAL</b>	SEE REPRESENTATIVE								



221 Lint Lane Irwin, PA 15642 • P: 800-245-5564 F: 724-446-9252 • www.linttile.com