

PROPLUS



BOARDWALK



COASTLINE

PRO PLUS SPECIFICATIONS

PACKAGING

PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
7" x 48" - Micro Bevel Standard Emboss, 100% Virgin Phthalate Free	12	28.36	1701.6	60	4.2mm	20	34,026	50"x40"x40"	45,000

PRODUCT

PERFORMANCE

COLLECTION	ProPlus	TEST PERFORMED	ASTM/ISO	RATING
CONSTRUCTION	Rigid Core SPC + EVA	DIMENSIONAL STABILITY	ISO 23999	≤1.67mm/m
LOCKING SYSTEM	14F	ABRASION RESISTANCE	ASTM D3884	AC2
WEAR LAYER	12 mil	APPLICATION	EN ISO 10874	22+
THICKNESS	3.2mm SPC + 1mm EVA PAD	WEAR AND SCRATCH RESISTANCE	ISO45862-2	Rating 4
ATTACHED CUSHION	1mm EVA	HEAT WARPAGE	ASTM D3884 with H18	≤1.0mm(0.2mm)
INSTALLATION	Floating	SHRINKAGE	ASTM D3884 with H18	0.08%
COLORS	Boardwalk, Coastline	CLICK TENSION FORCE	ISO 24334	≥125N/150mm, 168 N/150mm
ENVIRONMENTAL		DELAMINATION	ASTM D3884 with H18	OK(No Layered)
INDOOR AIR QUALITY	UL Greenguard	WEAR LAYER	EN ISO 24346	AC2
WARRANTY		WEIGHT	EN ISO 24342	6.69 kg/m2
RESIDENTIAL	15YRS	PRODUCT THICKNESS	EN ISO 23447	4.2mm (.17 in.)
LIGHT COMMERCIAL	SEE REPRESENTATIVE			

PROPLUS

Luxury Vinyl Tile



PRO PLUS COASTLINE



LINT TILE

221 Lint Lane Irwin, PA 15642
 P: 800-245-5564 F: 724-446-9252
 www.linttile.com



LINT TILE

PRO PLUS
Boardwalk

Boardwalk
17.5x120cm / 7"x48"
12mil Wear Layer



PROPLUS
Coastline

Coastline
17.5x120cm / 7"x48"
12mil Wear Layer



PRO PLUS BOARDWALK



PRO PLUS COASTLINE