

OAKMONT HICKORY






OAKMONT HICKORY SPECIFICATIONS

PACKAGING

PRODUCT DESCRIPTION	PCS/CTN	LBS/CTN	CTNS/PLT	SF/CTN	SF/PLT
1/2" x 7.4" Engineered Wire Brushed Wood Flooring	Varies	50	36	28.06	1010.1

PRODUCT

COORDINATING TRIM PIECES

COLLECTION	OAKMONT HICKORY	FINISH	Aluminum Oxide		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
CONSTRUCTION	5 Ply Engineered 3mm Wear Layer	GLOSS LEVEL	Low Gloss 7% +/- .02	78"		78"	
THICKNESS	1/2"	EDGE	Micro Bevel	QUARTER ROUND		FLUSH STAIRNOSE	
WIDTH	7.400" +/- .003	PROFILE	TONGUE & GROOVE		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
SPECIES	HICKORY	INSTALL GRADE	Substrate < 12% RH	78"		78"	
TEXTURE	Wire Brushed	RADIANT HEAT	OK	THRESHOLD REDUCER		T-MOLDING	
PLANK LENGTH	Varies: 15" - 86.5"	AVG LENGTH	36" to 40"		<input checked="" type="checkbox"/>		
COLORS	Super Natural, Chestnut, Latte, Pristine, Dusk	VARIATION	MED	78"			
INSTALLATION METHOD	STAPLE, GLUE, FLOAT	GRADE	MILL RUN	FLUSH REDUCER			

WARRANTY

RESIDENTIAL	LIFETIME	COMMERCIAL	5 YR	
CERTIFIED	FloorScore®	GREENGUARD®		



LINT TILE

221 LINT LANE IRWIN, PA 15642
P: 800-245-5564 F: 724-446-9252
www.linttile.com