

THREE RIVERS OAK






THREE RIVERS OAK SPECIFICATIONS

PACKAGING

PRODUCT DESCRIPTION	PCS/CTN	LBS/CTN	CTNS/PLT	SF/CTN	SF/PLT
3/4" x 3 1/4" Smooth Solid	Varies	65	40	22.5	900
3/4" x 5" Smooth Solid	Varies	67	40	23.5	940
1/2" x 5.4" Smooth Engineered	Varies	63	32	35.1	1123.2

PRODUCT

COORDINATING TRIM PIECES - 78"

COLLECTION	THREE RIVERS OAK		FINISH	Aluminum Oxide		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
CONSTRUCTION	Solid & 5 Ply Engineered (3mm wear layer)		GLOSS LEVEL	Low Gloss 7% +/- .02		78"		78"
THICKNESS	SOL	3/4"	EDGE	Micro Bevel	QUARTER ROUND		FLUSH STAIRNOSE	
	ENG	1/2"						
WIDTH	SOL	3 1/4" or 5"	PROFILE	TONGUE & GROOVE		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
	ENG	5.4" +/- .003						
SPECIES	WHITE AND RED OAK		INSTALL GRADE	Substrate < 12% RH		78"		78"
TEXTURE	Smooth		RADIANT HEAT	SOL-NO	THRESHOLD REDUCER		T-MOLDING	
PLANK LENGTH	SOL	Varies: 9" - 84"	AVG LENGTH	SOL	32"		<input checked="" type="checkbox"/>	
	ENG	Varies: 15" - 86.5"		ENG	36" - 40"			
COLORS	Canyon, Natural White Oak, Greystone, Boulder		VARIATION	MED - HIGH		78"		
INSTALLATION METHOD	SOL	Nail	GRADE	MILL RUN	FLUSH REDUCER			
	ENG	Staple, Glue or Float						

WARRANTY

RESIDENTIAL	LIFETIME		
CERTIFIED	FloorScore®	GREENGUARD®	



LINT TILE

221 LINT LANE IRWIN, PA 15642

P: 800-245-5564 F: 724-446-9252

www.linttile.com