

THREE RIVERS OAK



THREE RIVERS OAK Canyon (RH)



Canyon (RH)
3/4" x 3 1/4" & 5" Solid
1/2" x 5.4" Engineered
Smooth Texture Wood

COLOR DISPLAYED ON FRONT

THREE RIVERS OAK Natural White Oak (BB)



Natural White Oak (BB)
3/4" x 3 1/4" & 5" Solid
1/2" x 5.4" Engineered
Smooth Texture Wood

COLOR DISPLAYED ON FRONT

THREE RIVERS OAK Greystone (HI)



Greystone (HI)
3/4" x 3 1/4" & 5" Solid
1/2" x 5.4" Engineered
Smooth Texture Wood

COLOR DISPLAYED ON FRONT

THREE RIVERS OAK Boulder (WH)



Boulder (WH)
3/4" x 3 1/4" & 5" Solid
1/2" x 5.4" Engineered
Smooth Texture Wood

COLOR DISPLAYED ON FRONT - ENGINEERED

THREE RIVERS OAK SPECIFICATIONS

PACKAGING						
PRODUCT DESCRIPTION	PCS/CTN	LBS/CTN	CTNS/PLT	SF/CTN	SF/PLT	
3/4" x 3 1/4" Smooth Solid	Varies	65	40	22.5	900	
3/4" x 5" Smooth Solid	Varies	67	40	23.5	940	
1/2" x 5.4" Smooth Engineered	Varies	63	32	35.1	1123.2	
PRODUCT			COORDINATING TRIM PIECES - 78"			
COLLECTION	THREE RIVERS OAK		FINISH	Aluminum Oxide	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CONSTRUCTION	Solid & 5 Ply Engineered with 3mm wear layer		GLOSS LEVEL	Low Gloss 7% +/- .02	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
THICKNESS	Solid	3/4"	EDGE	Micro Bevel	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Engineered	1/2"	PROFILE	TONGUE & GROOVE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
WIDTH	Solid	3 1/4" or 5"	INSTALL GRADE	Substrate < 12% RH	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Engineered	5.4" +/- .003	RADIANT HEAT	SOL-NO	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SPECIES	WHITE AND RED OAK		AVG LENGTH	SOL 32" ENG 36"	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
TEXTURE	Smooth		VARIATION	MED - HIGH	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
PLANK LENGTH	Solid	Varies: 9" - 84"	GRADE	MILL RUN	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Engineered	Varies: 15" - 86.5"	INSTALLATION METHOD	Solid: Nail Engineered: Staple, Glue or Float	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
COLORS	Canyon, Natural White Oak, Greystone, Boulder		FLUSH REDUCER		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
WARRANTY						
RESIDENTIAL			LIFETIME		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CERTIFIED	FloorScore®		GREENGUARD®		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>



221 Lint Lane Irwin, PA 15642 • P: 800-245-5564 F: 724-446-9252 • www.linttile.com

