

LUXE EMERALD COAST

FLOATING SPC LVT FLOORING

Size - 7" x 48"

Overall thickness - 5mm

Wear Layer - 20mil

Painted Bevel - Yes

Attached Pad -

1mm IXPE

Installation-

Floating Click/Unilin™

Certifications-

UL Greenguard

10 PCS/CTN

24.03 SQFT/CTN

55 CTNS/PLT

1321.65 SQFT/PLT



LUXE SHERMAN'S LANDING

FLOATING SPC LVT FLOORING

Size - 7" x 48"

Overall thickness - 5mm

Wear Layer - 20mil

Painted Bevel - Yes

Attached Pad -
1mm IXPE

Installation-
Floating Click/Unilin™

Certifications-
UL Greenguard

10 PCS/CTN

24.03 SQFT/CTN

55 CTNS/PLT

1321.65 SQFT/PLT



 **LINT TILE**

LUXE WILD WOOD

FLOATING SPC LVT FLOORING

Size - 7" x 48"

Overall thickness - 5mm

Wear Layer - 20mil

Painted Bevel - Yes

Attached Pad -
1mm IXPE

Installation-
Floating Click/Unilin™

Certifications-
UL Greenguard

10 PCS/CTN

24.03 SQFT/CTN

55 CTNS/PLT

1321.65 SQFT/PLT



LUXE WINDY PINES

FLOATING SPC LVT FLOORING

Size - 7" x 48"

Overall thickness - 5mm

Wear Layer - 20mil

Painted Bevel - Yes

Attached Pad -

1mm IXPE

Installation-

Floating Click/Unilin™

Certifications-

UL Greenguard

10 PCS/CTN

24.03 SQFT/CTN

55 CTNS/PLT

1321.65 SQFT/PLT



LUXE XL GLACIER

RIGID CORE WATERPROOF LVT FLOORING

Size - 9" x 60"
Overall thickness - 5.5mm
Wear Layer - 20mil
Painted Bevel - Yes
Attached Pad -
 1mm IXPE
Installation-
 Floating /Unilin™
Certifications-
 UL Greenguard

7 PCS/CTN
26.24 SQFT/CTN
60 CTNS/PLT
1574.40 SQFT/PLT



LUXE XL MORNING DEW

RIGID CORE WATERPROOF LVT FLOORING

Size - 9" x 60"
Overall thickness - 5.5mm
Wear Layer - 20mil
Painted Bevel - Yes
Attached Pad -
 1mm IXPE
Installation-
 Floating /Unilin™
Certifications-
 UL Greenguard

7 PCS/CTN
26.24 SQFT/CTN
60 CTNS/PLT
1574.40 SQFT/PLT



LUXE XL RECLAIMED

RIGID CORE WATERPROOF LVT FLOORING

Size - 9" x 60"

Overall thickness - 5.5mm

Wear Layer - 20mil

Painted Bevel - Yes

Attached Pad -

1mm IXPE

Installation-

Floating /Unilin™

Certifications-

UL Greenguard

7 PCS/CTN

26.24 SQFT/CTN

60 CTNS/PLT

1574.40 SQFT/PLT



LUXE XL SEQUOIA

RIGID CORE WATERPROOF LVT FLOORING

Size - 9" x 60"
Overall thickness - 5.5mm
Wear Layer - 20mil
Painted Bevel - Yes
Attached Pad -
 1mm IXPE
Installation-
 Floating /Unilin™
Certifications-
 UL Greenguard

7 PCS/CTN
26.24 SQFT/CTN
60 CTNS/PLT
1574.40 SQFT/PLT



LUXE XL SHENANDOAH

RIGID CORE WATERPROOF LVT FLOORING

Size - 9" x 60"
Overall thickness - 5.5mm
Wear Layer - 20mil
Painted Bevel - Yes
Attached Pad -
 1mm IXPE
Installation-
 Floating /Unilin™
Certifications-
 UL Greenguard

7 PCS/CTN
26.24 SQFT/CTN
60 CTNS/PLT
1574.40 SQFT/PLT



LUXE XL SUNSET

RIGID CORE WATERPROOF LVT FLOORING

Size - 9" x 60"
Overall thickness - 5.5mm
Wear Layer - 20mil
Painted Bevel - Yes
Attached Pad -
 1mm IXPE
Installation-
 Floating /Unilin™
Certifications-
 UL Greenguard

7 PCS/CTN
26.24 SQFT/CTN
60 CTNS/PLT
1574.40 SQFT/PLT



LUXE XL VINEYARD

RIGID CORE WATERPROOF LVT FLOORING

Size - 9" x 60"
Overall thickness - 5.5mm
Wear Layer - 20mil
Painted Bevel - Yes
Attached Pad -
 1mm IXPE
Installation-
 Floating /Unilin™
Certifications-
 UL Greenguard

7 PCS/CTN
26.24 SQFT/CTN
60 CTNS/PLT
1574.40 SQFT/PLT



LUXE XL YELLOWSTONE

RIGID CORE WATERPROOF LVT FLOORING

Size - 9" x 60"
Overall thickness - 5.5mm
Wear Layer - 20mil
Painted Bevel - Yes
Attached Pad -
 1mm IXPE
Installation-
 Floating /Unilin™
Certifications-
 UL Greenguard

7 PCS/CTN
26.24 SQFT/CTN
60 CTNS/PLT
1574.40 SQFT/PLT



LUXE XL YOSEMITE

RIGID CORE WATERPROOF LVT FLOORING

Size - 9" x 60"
Overall thickness - 5.5mm
Wear Layer - 20mil
Painted Bevel - Yes
Attached Pad -
 1mm IXPE
Installation-
 Floating /Unilin™
Certifications-
 UL Greenguard

7 PCS/CTN
26.24 SQFT/CTN
60 CTNS/PLT
1574.40 SQFT/PLT



MACH I AVIATOR

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 8mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH I BOGEY

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 8mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



SCAN ME



LINT TILE

MACH I DOG FIGHT

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 8mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH I PARACHUTE

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 8mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH I PILOT

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 8mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH II BANDIT

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 12mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH II COMBAT

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 12mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH II FRAGGED

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 12mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH II FUSELAGE

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 12mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH II RIPCORD

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 12mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH II SUPER SONIC

GLUE DOWN LVT FLOORING

Size - 7" x 48"

100% Virgin Anti-microbial LVP

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 2mm

Wear Layer - 12mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

14 PCS/CTN

32.7 SQFT/CTN

85 CTNS/PLT

2,779.50 SQFT/PLT



MACH III FALCON #90

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 7" x 48"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III GOLDEN EAGLE #94

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 7" x 48"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score



SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III HELLFIRE #77

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 7" x 48"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score



SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III HORNET #92

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 7" x 48"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score



SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III LIGHTNING #95

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 7" x 48"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III RAPTOR #91

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 7" x 48"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III SOUND BARRIER #76

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 7" x 48"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III STEALTH #74

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 7" x 48"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III TOMCAT #93

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 7" x 48"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III GHOST RIDER #T90

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 36" x 36"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score



SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III TYPHOON #T91

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 36" x 36"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III PUNCH OUT #T92

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 18" x 36"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III TAILHOOK #T94

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 18" x 36"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MACH III WINCHESTER #T93

HEAVY COMMERCIAL GLUE DOWN LVT FLOORING

Size - 18" x 36"

Construction - Dimensionally Stable Core

Finish - ArmourGuard™ Microbead Technology

Overall thickness - 3mm

Wear Layer - 20mil

Installation-

Direct Glue / PSA

Certifications-

Floor Score

SIZES	PC/CTN	SQFT/CTN	CTNS/PLT	SQFT/PLT
7" x 48"	12	28	65	1820
36" x 36"	6	54	35	1890
18" x 36"	10	45	42	1890



MEDITERRANEAN ROME 800

WATERPROOF LVT FLOORING

Size - 12" x 24"

Overall thickness - 6.5mm

Wear Layer - 20mil

Finish - Medium Gloss

Painted Bevel - Yes

Attached Pad -

Quiet Step Cushion+™

Installation-

Floating Click/Unilin

Certifications-

Greenguard

Floor Score



12 PCS/CTN

24.03 SQFT/CTN

48 CTNS/PLT

1153.44 SQFT/PLT

TRI  CORE™
W A T E R P R O O F

 **LINT TILE**

MEDITERRANEAN NAPLES 801

WATERPROOF LVT FLOORING

Size - 12" x 24"

Overall thickness - 6.5mm

Wear Layer - 20mil

Finish - Medium Gloss

Painted Bevel - Yes

Attached Pad -

Quiet Step Cushion+™

Installation-

Floating Click/Unilin

Certifications-

Greenguard

Floor Score



12 PCS/CTN

24.03 SQFT/CTN

48 CTNS/PLT

1153.44 SQFT/PLT

TRICORE™
W A T E R P R O O F

 **LINT TILE**

MEDITERRANEAN TIVOLI 802

WATERPROOF LVT FLOORING

Size - 12" x 24"

Overall thickness - 6.5mm

Wear Layer - 20mil

Finish - Medium Gloss

Painted Bevel - Yes

Attached Pad -

Quiet Step Cushion+™

Installation-

Floating Click/Unilin

Certifications-

Greenguard

Floor Score



12 PCS/CTN

24.03 SQFT/CTN

48 CTNS/PLT

1153.44 SQFT/PLT

TRICORE™
W A T E R P R O O F

The logo for LINT TILE, featuring a stylized red diamond shape on the left with horizontal lines, followed by the text "LINT TILE" in a large, bold, red, italicized serif font.

MEDITERRANEAN PALERMO 803

WATERPROOF LVT FLOORING

Size - 12" x 24"

Overall thickness - 6.5mm

Wear Layer - 20mil

Finish - Medium Gloss

Painted Bevel - Yes

Attached Pad -

Quiet Step Cushion+™

Installation-

Floating Click/Unilin

Certifications-

Greenguard

Floor Score



12 PCS/CTN

24.03 SQFT/CTN

48 CTNS/PLT

1153.44 SQFT/PLT

TRICORE™
W A T E R P R O O F

The logo for LINT TILE, featuring a stylized red diamond shape on the left with horizontal lines, followed by the text "LINT TILE" in a large, bold, red, italicized serif font.

MEDITERRANEAN TUSCANY 804

WATERPROOF LVT FLOORING

Size - 12" x 24"

Overall thickness - 6.5mm

Wear Layer - 20mil

Finish - Medium Gloss

Painted Bevel - Yes

Attached Pad -

Quiet Step Cushion+™

Installation-

Floating Click/Unilin

Certifications-

Greenguard

Floor Score



12 PCS/CTN

24.03 SQFT/CTN

48 CTNS/PLT

1153.44 SQFT/PLT

TRICORE™
W A T E R P R O O F

The logo for LINT TILE, featuring a stylized red diamond shape on the left with horizontal lines, followed by the words "LINT TILE" in a large, bold, red, italicized serif font.

MEDITERRANEAN TOSCANO 805

WATERPROOF LVT FLOORING

Size - 12" x 24"

Overall thickness - 6.5mm

Wear Layer - 20mil

Finish - Medium Gloss

Painted Bevel - Yes

Attached Pad -

Quiet Step Cushion+™

Installation-

Floating Click/Unilin

Certifications-

Greenguard

Floor Score



12 PCS/CTN

24.03 SQFT/CTN

48 CTNS/PLT

1153.44 SQFT/PLT

TRICORE™
W A T E R P R O O F

The logo for LINT TILE, featuring a stylized red diamond shape with horizontal lines on the left, followed by the words "LINT TILE" in a large, bold, red, italicized serif font.

PROPLUS BOARDWALK

FLOATING LVT FLOORING

Size - 7" x 48"

100% Virgin Standard Emboss

Construction - Rigid Core SPC + EVA

Locking System - 14F

Overall thickness - 4.2mm

Attached Cushion - 1mm EVA

Wear Layer - 12mil

Installation-

Floating

Certifications-

UL Greenguard

12 PCS/CTN

28.36 SQFT/CTN

60 CTNS/PLT

1701.6 SQFT/PLT



PROPLUS COASTLINE

FLOATING LVT FLOORING

Size - 7" x 48"

100% Virgin Standard Emboss

Construction - Rigid Core SPC + EVA

Locking System - 14F

Overall thickness - 4.2mm

Attached Cushion - 1mm EVA

Wear Layer - 12mil

Installation-

Floating

Certifications-

UL Greenguard

12 PCS/CTN

28.36 SQFT/CTN

60 CTNS/PLT

1701.6 SQFT/PLT



SPIRE BERLIN

SPC FLOATING/GLUEDOWN LVT FLOORING

Size - 7" x 48"

Value Engineered SPC Flooring Quantum X Technology
Construction - SPC

Locking System - Unilin™

Overall thickness - 4.7mm

Underlayment - 1.2mm IXPE (NO VOC)

Wear Layer - 12mil with QXT

Installation-

Floating, Glue Down

Certifications-

Floor Score

12 PCS/CTN

28.365 SQFT/CTN

50 CTNS/PLT

1418.25 SQFT/PLT



SPIRE CANCUN

SPC FLOATING/GLUEDOWN LVT FLOORING

Size - 7" x 48"

Value Engineered SPC Flooring Quantum X Technology

Construction - SPC

Locking System - Unilin™

Overall thickness - 4.7mm

Underlayment - 1.2mm IXPE (NO VOC)

Wear Layer - 12mil with QXT

Installation-

Floating, Glue Down

Certifications-

Floor Score

12 PCS/CTN

28.365 SQFT/CTN

50 CTNS/PLT

1418.25 SQFT/PLT



SPIRE COPA

SPC FLOATING/GLUEDOWN LVT FLOORING

Size - 7" x 48"

Value Engineered SPC Flooring Quantum X Technology
Construction - SPC

Locking System - Unilin™

Overall thickness - 4.7mm

Underlayment - 1.2mm IXPE (NO VOC)

Wear Layer - 12mil with QXT

Installation-

Floating, Glue Down

Certifications-

Floor Score

12 PCS/CTN

28.365 SQFT/CTN

50 CTNS/PLT

1418.25 SQFT/PLT



SPIRE DUBLIN

SPC FLOATING/GLUEDOWN LVT FLOORING

Size - 7" x 48"

Value Engineered SPC Flooring Quantum X Technology
Construction - SPC

Locking System - Unilin™

Overall thickness - 4.7mm

Underlayment - 1.2mm IXPE (NO VOC)

Wear Layer - 12mil with QXT

Installation-

Floating, Glue Down

Certifications-

Floor Score

12 PCS/CTN

28.365 SQFT/CTN

50 CTNS/PLT

1418.25 SQFT/PLT

