



MEDITERRANEAN



COLOR DISPLAYED ON FRONT



COLOR DISPLAYED ON FRONT



COLOR DISPLAYED ON FRONT



COLOR DISPLAYED ON FRONT



COLOR DISPLAYED ON FRONT



COLOR DISPLAYED ON FRONT



MEDITERRANEAN SPECIFICATIONS									
PACKAGING									
PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	CTNS/CTNR	LBS/CTNR
12" x 24" - Light Commercial Waterproof Tri-Core™ LVT	12	24.03	1153.44	48	6.5mm	20	23,068.80	960	N/A
PRODUCT					PERFORMANCE				
COLLECTION	Mediterranean			TEST PERFORMED	ASTM	RATING			
CONSTRUCTION	Waterproof Tri Core™			SIZE	F2055	PASS			
FINISH	Medium Gloss			THICKNESS	F386	PASS			
WEAR LAYER	20 mil (.5mm)			SQUARENESS	F2055	PASS			
THICKNESS	6.5mm			DIMENSIONAL STABILITY	F2199	PASS 0.011 in/ft			
ATTACHED CUSHION	Quiet Step Cushion+™			RESIDUAL INDENTATION	F1914	PASS			
INSTALLATION	Floating Click / Unilin™			STATIC LOAD LIMIT	F970	PASS 1000psi/250psi			
COLORS	Rome 801, Naples801, Tivoli 802, Palermo 803, Tuscany 804, Tuscano 805			FLEXIBILITY	F137	PASS			
ENVIRONMENTAL				RESISTANCE TO HEAT	F1514	PASS < 8 (delta E)			
INDOOR AIR QUALITY				RESISTANCE TO LIGHT	1515	PASS < 8 (delta E)			
Floor Score, Green-guard				RESISTANCE TO CHEMICALS	F925	PASS			
WARRANTY				CRITICAL RADIANT FLUX	E648	CLASS 1 < 0.45w/cm²			
RESIDENTIAL	Limited Lifetime			OPTICAL SMOKE DENSITY	E662	PASS < 450			
COMMERCIAL	15YRS			SLIP RESISTANCE	C1028	PASS (> 0.50)			



SCAN ME



221 LINT LANE IRWIN, PA 15642 • P: 800-245-5564 • www.linttile.com