

FOREST

5mm Luxury Vinyl Plank



FOREST - DRIFTWOOD

FOREST DRIFTWOOD




FOREST DRIFTWOOD
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

FOREST GOLDEN OAK



FOREST GOLDEN OAK
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

FOREST SILVER MAPLE




FOREST SILVER MAPLE
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

FOREST NATURAL PINE



FOREST NATURAL PINE
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

FOREST WARM CHESTNUT



FOREST WARM CHESTNUT
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER



LINT TILE

FOREST HD



FOREST HD SPECIFICATIONS

PACKAGING

PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
7" x 48" - Luxury Vinyl Plank Acoustic Cushioning	4	32.68	1797.19	55	5mm	20	35943.78	49"x40"x37"	51,280

PRODUCT

PERFORMANCE

COLLECTION	Forest	TEST PERFORMED	ASTM	RATING
CONSTRUCTION	LVP	IMPACT SOUND CONDUCTION	E492-09	62
LOCKING SYSTEM	N/A	SOUND TRANSMISSION CLASS	E90-09	64
WEAR LAYER	20 mil (.5mm)	SLIP RESISTANCE	D2047	>0.8 Low Risk
THICKNESS	4mm + 1mm pad	DIMENSIONAL STABILITY	F2199	PASS <.02"/ft
ATTACHED CUSHION	1mm IXPE	RESIDUAL INDENTATION	F1914	PASS
INSTALLATION	Direct Glue Down	STATIC LOAD LIMIT	F970	PASS
COLORS	Golden Oak, Silver Maple, Warm Chestnut, Natural Pine, Driftwood	FLEXIBILITY	F137	PASS
ENVIRONMENTAL		RESISTANCE TO HEAT	F1514	PASS
INDOOR AIR QUALITY	UL Greenguard	RESISTANCE TO LIGHT	1515	PASS
WARRANTY		RESISTANCE TO CHEMICALS	F925	5min - PASS 24hr - PASS
RESIDENTIAL	25YRS	RADIANT FLUX	648	EXCEEDS CLASS 1
LIGHT COMMERCIAL	20YRS	SMOKE DENSITY	E662	PASS



LINT TILE

221 Lint Lane Irwin, PA 15642
P: 800-245-5564 F: 724-446-9252
www.linttile.com



SCAN ME