


FOREST

5mm Luxury Vinyl Plank



FOREST - DRIFTWOOD

FOREST DRIFTWOOD



FOREST DRIFTWOOD
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

FOREST NATURAL PINE




FOREST NATURAL PINE
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

FOREST GOLDEN OAK




FOREST GOLDEN OAK
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

FOREST WARM CHESTNUT



FOREST WARM CHESTNUT
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

FOREST SILVER MAPLE



FOREST SILVER MAPLE
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER



LINT TILE

FOREST HD



GOLDEN OAK



SILVER MAPLE



NATURAL PINE



WARM CHESNUT



DRIFTWOOD

FOREST HD SPECIFICATIONS

PACKAGING

PRODUCT DESCRIPTION		PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
7" × 48" - Luxury Vinyl Plank Acoustic Cushioning		4	32.68	1797.19	55	5mm	20	35943.78	49"x40"x37"	51,280
PRODUCT				PERFORMANCE						
COLLECTION		Forest		TEST PERFORMED			ASTM		RATING	
CONSTRUCTION		LVP		IMPACT SOUND CONDUCTION			E492-09		62	
LOCKING SYSTEM		N/A		SOUND TRANSMISSION CLASS			E90-09		64	
WEAR LAYER		20 mil (.5mm)		SLIP RESISTANCE			D2047		>0.8 Low Risk	
THICKNESS		3.5mm + 1.5mm pad		DIMENSIONAL STABILITY			F2199		PASS <.02"/ft	
ATTACHED CUSHION		1mm IXPE		RESIDUAL INDENTATION			F1914		PASS	
INSTALLATION		Direct Glue Down		STATIC LOAD LIMIT			F970		PASS	
COLORS	Golden Oak, Silver Maple, Warm Chestnut, Natural Pine, Driftwood			FLEXIBILITY			F137		PASS	
ENVIRONMENTAL				RESISTANCE TO HEAT			F1514		PASS	
INDOOR AIR QUALITY		UL Greenguard		RESISTANCE TO LIGHT			1515		PASS	
WARRANTY				RESISTANCE TO CHEMICALS			F925		5min - PASS	24hr - PASS
RESIDENTIAL		25YRS		RADIANT FLUX			648		EXCEEDS CLASS 1	
LIGHT COMMERCIAL		20YRS		SMOKE DENSITY			E662		PASS	



LINT TILE

221 Lint Lane Irwin, PA 15642
P: 800-245-5564 F: 724-446-9252
www.linttile.com



SCAN ME