





**FOREST
DRIFTWOOD**




FOREST DRIFTWOOD
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

**FOREST
GOLDEN OAK**




FOREST GOLDEN OAK
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

**FOREST
SILVER MAPLE**




FOREST SILVER MAPLE
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

**FOREST
NATURAL PINE**



FOREST NATURAL PINE
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER

**FOREST
WARM CHESTNUT**



FOREST WARM CHESTNUT
17.5x120cm / 7"x48"
5 MM (4MM + 1MM IXPE) LVP
20 MIL WEAR LAYER



LINT TILE



FOREST HD



GOLDEN OAK



SILVER MAPLE



NATURAL PINE



WARM CHESNUT



DRIFTWOOD

FOREST HD SPECIFICATIONS

PACKAGING

PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
7" × 48" - Luxury Vinyl Plank Acoustic Cushioning	4	32.68	1797.19	55	5mm	20	35943.78	49"x40"x37"	51,280

PRODUCT

PERFORMANCE

COLLECTION		Forest	TEST PERFORMED	ASTM	RATING	
CONSTRUCTION		LVP	IMPACT SOUND CONDUCTION	E492-09	62	
LOCKING SYSTEM		N/A	SOUND TRANSMISSION CLASS	E90-09	64	
WEAR LAYER		20 mil (.5mm)	SLIP RESISTANCE	D2047	>0.8 Low Risk	
THICKNESS		3.5mm + 1.5mm pad	DIMENSIONAL STABILITY	F2199	PASS <.02”/ft	
ATTACHED CUSHION		1mm IXPE	RESIDUAL INDENTATION	F1914	PASS	
INSTALLATION		Direct Glue Down	STATIC LOAD LIMIT	F970	PASS	
COLORS	Golden Oak, Silver Maple, Warm Chestnut, Natural Pine, Driftwood		FLEXIBILITY	F137	PASS	
ENVIRONMENTAL			RESISTANCE TO HEAT	F1514	PASS	
INDOOR AIR QUALITY		UL Greenguard	RESISTANCE TO LIGHT	1515	PASS	
WARRANTY			RESISTANCE TO CHEMICALS	F925	5min - PASS	24hr - PASS
RESIDENTIAL		25YRS	RADIANT FLUX	648	EXCEEDS CLASS 1	
LIGHT COMMERCIAL		20YRS	SMOKE DENSITY	E662	PASS	



LINT TILE

221 Lint Lane Irwin, PA 15642
P: 800-245-5564 F: 724-446-9252
www.linttile.com



SCAN ME

