

# SOUNDLOCK II FAWN

**SOUNDLOCK II**  
Fawn

Fawn  
17.5x120cm / 7"x48"  
20mil Wear Layer  
#NS-SL2 7X48-FA



LINT SURE SET  
Multipurpose Flooring Adhesive  
4 Gallons (#LTA-SS4)  
1 Gallon (#LTA-SS1)



Ready-to-Use  
Lint Hardwood & LVT  
Floor Cleaner (#LTC-WL)

## SOUNDLOCK II SPECIFICATIONS

PACKAGING									
PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
7" x 48" - Luxury Vinyl Plank with attached IXPE pad Random Embossed	20	48.05	2883	60	4mm	15	43,245	48x40x45	42,750
PRODUCT					PERFORMANCE				
<b>COLLECTION</b>	SoundLock II				<b>TEST PERFORMED</b>	ASTM		RATING	
<b>CONSTRUCTION</b>	ESPC				<b>IMPACT SOUND CONDUCTION</b>	E492-09		62	
<b>FINISH</b>	ArmourGuard™				<b>SOUND TRANSMISSION CLASS</b>	E90-09		64	
<b>WEAR LAYER</b>	20 mil (.5mm)				<b>SLIP RESISTANCE</b>	D2047		>0.8 Low Risk	
<b>THICKNESS</b>	4 mm (w/ pad)				<b>DIMENSIONAL STABILITY</b>	F2199		PASS <.02"/ft	
<b>ATTACHED CUSHION</b>	IXPE				<b>RESIDUAL INDENTATION</b>	F1914		PASS	
<b>INSTALLATION</b>	Glue Down				<b>STATIC LOAD LIMIT</b>	F970		PASS	
<b>COLORS</b>	Fawn, Silver Fox				<b>FLEXIBILITY</b>	F137		PASS	
ENVIRONMENTAL					<b>RESISTANCE TO HEAT</b>	F1514		PASS	
<b>INDOOR AIR QUALITY</b>	Floor Score				<b>RESISTANCE TO LIGHT</b>	1515		PASS	
WARRANTY					<b>RESISTANCE TO CHEMICALS</b>	F925		5min - PASS	24hr - PASS
<b>RESIDENTIAL</b>	See Representative				<b>RADIANT FLUX</b>	648		PASS	
<b>LIGHT COMMERCIAL</b>	See Representative				<b>SMOKE DENSITY</b>	E662		PASS	

### AVAILABLE TRIM PIECES



1-3/4" x 5/16" T-Mold

1-3/4" x 5/16" Reducer

1-1/4" x 5/16" End-Cap

2" x 1" Stairnose



221 Lint Lane • Irwin, PA 15642 • 1-800-245-5564 • www.linttile.com



SCAN ME