



SOUNDLOCK II SILVER FOX

SOUNDLOCK II
Silver Fox

Silver Fox
17.5x120cm / 7"x48"
20mil Wear Layer
#NS-SL2 7X48-SI



LINT SURE SET
Multipurpose Flooring Adhesive
4 Gallons (#LTA-SS4)
1 Gallon (#LTA-SS1)



Ready-to-Use
Lint Hardwood & LVT
Floor Cleaner (#LTC-WL)

SOUNDLOCK II SPECIFICATIONS									
PACKAGING									
PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
7" x 48" - Luxury Vinyl Plank with attached IXPE pad Random Embossed	20	48.05	2883	60	4mm	15	43,245	48x40x45	42,750
PRODUCT					PERFORMANCE				
COLLECTION	SoundLock II			TEST PERFORMED	ASTM		RATING		
CONSTRUCTION	ESPC			IMPACT SOUND CONDUCTION	E492-09		62		
FINISH	ArmourGuard™			SOUND TRANSMISSION CLASS	E90-09		64		
WEAR LAYER	20 mil (.5mm)			SLIP RESISTANCE	D2047		>0.8 Low Risk		
THICKNESS	4 mm (w/ pad)			DIMENSIONAL STABILITY	F2199		PASS <.02"/ft		
ATTACHED CUSHION	IXPE			RESIDUAL INDENTATION	F1914		PASS		
INSTALLATION	Glue Down			STATIC LOAD LIMIT	F970		PASS		
COLORS	Fawn, Silver Fox			FLEXIBILITY	F137		PASS		
ENVIRONMENTAL				RESISTANCE TO HEAT	F1514		PASS		
INDOOR AIR QUALITY	Floor Score			RESISTANCE TO LIGHT	1515		PASS		
WARRANTY				RESISTANCE TO CHEMICALS	F925		5min - PASS		24hr - PASS
RESIDENTIAL	See Representative			RADIANT FLUX	648		PASS		
LIGHT COMMERCIAL	See Representative			SMOKE DENSITY	E662		PASS		

AVAILABLE TRIM PIECES



221 Lint Lane • Irwin, PA 15642 • 1-800-245-5564 • www.linttile.com



SCAN ME