

FOREST HD



FOREST HD SPECIFICATIONS

PACKAGING

PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
7" x 48" - Luxury Vinyl Plank Acoustic Cushioning Embossed in Register (EIR) Painted Bevel	14	32.68	1797.19	55	5mm	20	35943.78	49"x40"x37"	51,280

PRODUCT

PERFORMANCE

COLLECTION	Forest	TEST PERFORMED	ASTM	RATING
CONSTRUCTION	LVP	IMPACT SOUND CONDUCTION	E492-09	62
LOCKING SYSTEM	N/A	SOUND TRANSMISSION CLASS	E90-09	64
WEAR LAYER	20 mil (.5mm)	SLIP RESISTANCE	D2047	>0.8 Low Risk
THICKNESS	3.5mm + 1.5mm pad	DIMENSIONAL STABILITY	F2199	PASS <.02"/ft
ATTACHED CUSHION	1.5mm pad, IXPE	RESIDUAL INDENTATION	F1914	PASS
INSTALLATION	Direct Glue Down	STATIC LOAD LIMIT	F970	PASS
COLORS	Golden Oak, Silver Maple, Warm Chestnut, Natural Pine, Driftwood	FLEXIBILITY	F137	PASS
ENVIRONMENTAL		RESISTANCE TO HEAT	F1514	PASS
INDOOR AIR QUALITY	UL Greenguard	RESISTANCE TO LIGHT	1515	PASS
WARRANTY		RESISTANCE TO CHEMICALS	F925	5min - PASS 24hr - PASS
RESIDENTIAL	25YRS	RADIANT FLUX	648	EXCEEDS CLASS 1
LIGHT COMMERCIAL	20YRS	SMOKE DENSITY	E662	PASS



221 Lint Lane • Irwin, PA 15642 • 1-800-245-5564 • www.linttile.com

